



XF-PTL11057-M72-11.48-VI

Optional camera mount
 1、 M58×0.75
 2、 M72×0.75

Specification

Optical structure	Bi-Telecentric
Magnification	0.539
Object field of view	Φ106.5mm
Image field of view	Φ57.4mm
Working Distance	250mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	4.2mm@F11
F#	F8-F76
Resolution	13.5μm@F11
MTF	>0.3@95lp/mm@F11
Distortion	<0.043%(0.063%)
Detector type:	
35film 36×24	66.8×44.5mm
2' 23×23	42.7×42.7mm
4/3' 18×13.5	33.4×25.0mm
1.1' 14.2×10.4	26.3×19.3mm
2K Linear scan 2048×10μm	38.0mm
4K Linear scan 4096×7μm	53.2mm
8K Linear scan 8192×5μm	76.0mm
8K Linear scan 8192×7μm	106.4mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL11057-M72-11.48-VI-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	☐ ⊕
Modify2			Total:	Page: