



XF-PTL15257-M72-11.48-VI

Optional camera mount
 1、 M58×0.75
 2、 M72×0.75

Specification

Optical structure	Bi-Telecentric
Magnification	0.391
Object field of view	Φ146.8mm
Image field of view	Φ57.4mm
Working Distance	320mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	7.9mm@F11
F#	F6-F76
Resolution	18.6μm@F11
MTF	>0.3@95lp/mm@F11
Distortion	<0.032%(0.090%)
Detector type:	
35film 36×24	92.1×61.4mm
2' 23×23	58.8×58.8mm
4/3' 18×13.5	46.0×34.5mm
1.1' 14.2×10.4	36.3×26.6mm
2K Linear scan 2048×10μm	52.4mm
4K Linear scan 4096×7μm	73.3mm
8K Linear scan 8192×5μm	104.8mm
8K Linear scan 8192×7μm	146.7mm

XF-PTLAAABB-C/F/P/M- (L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV _____</p> <p>Image FOV _____</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p style="text-align: right;">90° Steering option</p>
--	--

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL15257-M72-11.48-VI-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	
Modify2			Total:	
			Page:	Canrill OPTICS

All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.