



XF-MH04X416

Specification

| | |
|----------------------|---------------|
| Magnification | 0.4 |
| Object field of view | Φ27.5mm |
| Image field of view | Φ11.0mm |
| Working Distance | 416mm±3% |
| Depth of field | 4.4mm |
| F# | F7 |
| Resolution | 11.6μm |
| MTF | >0.3@125lp/mm |
| Distortion | <0.009% |

Detector type:

| | | |
|--------|-----------|-------------|
| 2/3' | 8.45×7.07 | 21.1×17.7mm |
| 1/1.8' | 7.2×5.3 | 18.0×13.3mm |
| 1/2' | 6.4×4.8 | 16.0×12.0mm |
| 1/3' | 4.8×3.6 | 12.0×9.0mm |

| | | | | | |
|--------------------------|--------|------------------|---------------------|-------|---|
| Undefined tolerance (mm) | degree | File Name | | | |
| X. X | ±0.2 | ±30min | XF-MH04X416-外形尺寸-EN | | |
| X. XX | ±0.02 | Drawing Name | | | |
| X. XXX | ±0.005 | Drawing Size: A3 | | | |
| | Sign | Data/Ver. | Material | Ratio | Product Name |
| Design | | | | 1:1 | |
| Modify1 | | | Qty | | Canrill OPTICS |
| Modify2 | | | Total: | Page: | All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization. |